



# VRLA Battery **SPB 12-65**

<b>Specifications</b>	<b>Nominal Voltage</b>	12 V				
	<b>Rated Capacity (25 °C)</b>	<b>20hr Rate (1,80V/cell)</b>	<b>10hr Rate (1,80V/cell)</b>	<b>5hr Rate (1,70V/cell)</b>	<b>1hr Rate (1,60V/cell)</b>	
		68 Ah	65 Ah	55,5 Ah	41,5 Ah	
	<b>Dimensions (mm) &amp; Weight (kg)</b>	<b>Length</b>	<b>Width</b>	<b>Height</b>	<b>Overall Height</b>	<b>Weight</b>
		350mm	167mm	179mm	179mm	23,40 kg
	<b>Number / Type of Terminals</b>	2 / M6				

## Technical Characteristics

<b>Design Life at 20°C</b>	10-12 years	
<b>Eurobat Classification</b>	High Performance	
<b>Internal Resistance (Fully charged - 25°C)</b>	6 mΩ	
<b>Short-circuit current</b>	1700 A	
<b>Max Charging Current</b>	19,5 A	
<b>Min safe end Discharge Voltage</b>	1,60 V/cell	
<b>Self discharge per month at 20°C</b>	3%	
<b>Recommended Charging Voltage at 20°C</b>	Stand-by use (V/cell):	2,25 to 2,30
	Cycle use (V/cell):	2,40 to 2,50
<b>Container Material</b>	ABS-UL94 HB	
<b>Electrolyte Type</b>	Sulfuric Acid	
<b>Type of plates / Alloy</b>	Flat plates / Lead-Calcium-Tin alloy	
<b>Type of Separator</b>	Absorbant Glass Mat	
<b>Valve Type / Operational Pressure</b>	Rubber / 1-3 psi (70-200 mbar)	
<b>Operating Temperature Range</b>	-20 to + 50 °C	
<b>Storage time at 20°C</b>	9 months	

