



VRLA Battery **SPB 6-200**




Specifications

Nominal Voltage 6 V

Rated Capacity (25 °C)	20hr Rate (1,80V/cell)	10hr Rate (1,80V/cell)	5hr Rate (1,70V/cell)	1hr Rate (1,60V/cell)	
	198 Ah	182 Ah	170,5 Ah	136 Ah	
Dimensions (mm) & Weight (kg)	Length	Width	Height	Overall Height	Weight
	318mm	178mm	225mm	228mm	31 kg
Number / Type of Terminals 2 / M8					

Technical Characteristics

Design Life at 20°C	10-12 years
Eurobat Classification	High Performance
Internal Resistance (Fully charged - 25°C)	<2 mΩ
Short-circuit current	5000 A
Max Charging Current	50 A
Min safe end Discharge Voltage	1,60 V/cell
Self discharge per month at 20°C	3%
Recommended Charging Voltage at 20°C	Stand-by use (V/cell): 2,25 to 2,30 Cycle use (V/cell): 2,40 to 2,50
Container Material	ABS-UL94 HB
Electrolyte Type	Sulfuric Acid
Type of plates / Alloy	Flat plates / Lead-Calcium-Tin alloy
Type of Separator	Absorbant Glass Mat
Valve Type / Operational Pressure	Rubber / 1-3 psi (70-200 mbar)
Operating Temperature Range	-20 to + 50°C
Storage time at 20°C	9 months



SUNLIGHT
creating energy